

RS-232/422/485 TO Ethernet Converter

E-P132-X SPEC

FUNCTION

- RS-232/422/485 TO Ethernet Converter
- Digital TTL I/O Controlled Via Ethernet



SPEC

- CPU : 32-bits ARM-7 , 33 MHz
- RAM : 2 M Bytes (1 M*16Bits)
- ROM : 128 K Bytes
- Ethernet
 - Port : RJ-45 Connector
 - Lan : 10 /100 M bps (Auto Detecting)
 - Protocol : ARP, IP, ICMP, UDP, TCP, HTTP, DHCP, PPPoE
 - Mode : TCP Server/Client ; UDP Client
 - Setup : HTTP Browser Setup (IE & Netscape)
 - Security : Setup Password & Connect Password
- Serial Port
 - Port : RS-232 * 1 Port / RS-422/RS-485 * 1 Port
 - Built-in RS-422/RS-485 Terminal Register
 - Speed : 300 bps~230.4k bps
 - Parity : None , Odd , Even
 - Data Bit : 5 , 6 , 7 , 8
 - Stop Bit : 1 , 2
 - RS-232 Pins : Rx , Tx , GND , RTS , CTS , DTR , DSR , DCD
 - RS-422 : Rx+ , Rx- , Tx+ , Tx-
 - RS-485 : Data+ , Data-
- Digital I/O Port
 - TTL Digital I/O * 8
- Watch Dog Function
- Firmware On-lined Updated Via Ethernet
- Power : DC 9 V , 500mA
- Led Lamp : SYS(PWR) , LAN , LAN Rx , LAN Tx,
- Environment : Operating Temp: 0°C ~50°C Storage Temp : -10°C ~70°C
- Dimensions : 110 * 68 * 27 mm (W * D * H)
- WEIGHT : 140 gm